

# ID5002P Acoustic Pig Signaller



The ID5002 (Passive) is a fully ATEX and IECEx certified intrinsically safe non-intrusive pig signaller which quickly and accurately detects, signals and logs the passage of pigs at critical points along a pipeline both onshore and offshore.

## Key Benefits

- Removes any uncertainty over confirmation of pig passage.
- Suitable for all pig types - no transmitters are required to confirm passage.
- Quick and easy installation using ratchet strap or stainless steel banding.
- Suitable for gas and liquid pipelines.
- Main housing can be mounted remotely for use on buried pipelines or where access is limited.
- Seamlessly integrate with your control systems using RS485 MODBUS RTU bi-directional communications to receive notifications, pig passage information, and configure the signaller.
- Dedicated software provides real-time monitoring and instant readings facilitating debugging and testing and offering a deeper understanding of the theory of operation.

Interested in hearing more about this, or other applications?  
Contact our IK Trax specialists at:

IK Trax  
T: +44 (0)1224 714714  
E: Sales@iktrax.com

# ID5002P Acoustic Pig Signaller

The ID5002P monitors the acoustic emissions created by the vibrational and acoustic noise generated as a pig moves through a pipeline. The unit then processes the emissions to identify the signature of a passing pig. Events are signalled as they occur via a graphical display and high brightness LEDs positioned around the perimeter of the display. The unit logs the time and date of up to 99 events. Logged events can be viewed locally on the display or transmitted remotely over several optional interfaces. The user can turn the unit ON and OFF as well as modify several settings using the single control button and intuitive menu system.

The ID5002P has two basic parts - the main housing and sensor. The sensor is permanently connected to the main housing via a cable and can be quickly and easily attached to the pipeline using ratchet straps or steel banding. The main housing contains all electronics, display and the control button and can be mounted on the pipeline using a mounting plate or mounted on a wall or post.

## PRODUCT SPECIFICATION

External Supply	PSD5201 Intrinsically Safe Power Supply <sup>Note 1</sup>
Entries	3x M20x1.5
Enclosure Temperature Range	-40°C to +85°C (-40°F to +185°F)
Sensor Temperature Range	-55°C to +110°C (-67°F to +230°F)
Maximum Pipeline Surface Temperature	+150° (+302°F) <sup>Note 2</sup>
Typical Minimum Pig Speed	0.1m/s <sup>Note 3</sup>

## MATERIALS & DIMENSIONS

Housing Material	Aluminium or 316L Stainless Steel
Length (including mounting plate)	240mm (9.4")
Width (including mounting plate)	192mm (7.6")
Height (including mounting plate)	174mm (6.9")
Weight in Aluminium	8kg (17.6lbs)
Weight in 316L Stainless Steel	13kg (28.7lbs)
Cable Length	5 metre (16ft) or 10 metre (32ft)

## CERTIFICATION

ATEX Code	Ex II 1 G Ex ia IIB T4 Ga
IECEX Code	Ex ia IIB T4 Ga
EU Type Examination Cert No	EMT 16 ATEX 0007 X
UKEX Cert No	EMA 22 UKEX 0006 X
IECEX Cert No	IIECEX EMT 16.0006 X
Ingress Protection (Enclosure)	IP66
Ingress Protection (Sensor)	IP68

## STANDARD OUTPUTS

DPDT Relay (Volt Free Contacts)	2A @ 30VDC
Current Loop	4-20mA <sup>Note 4</sup>
Serial Data Interface	RS485 MODBUS RTU

Note 1 The ID5002P must be powered from a GM International PSD5201 power supply (power consumption <2.5W) which may be purchased separately from IK Trax.

Note 2 Maximum allowable pipeline surface temperature depends on ambient air temperature and mounting configuration. Only the sensor may be mounted on the pipeline

Note 3 Minimum pig speed depends on pig type, pipeline configuration and installation position

Note 4 Current loop levels are configurable between 4mA and 20mA. Default set state 20.0mA. Default reset state 4.0mA. Tolerance between ± 1.0mA.

Interested in hearing more about this, or other applications? Contact our IK Trax specialists at:

IK Trax  
T: +44 (0)1224 714714  
E: Sales@iktrax.com